

Roto's 4-point Locking System



Features & Benefits

- 2-point strike features 1/8" adjustability
- 1-point strike features 1/4" adjustability
- Robust hook-style locking points with two opposing primary hooks and an additional outward facing hook 28" from each side of the center line
- Anodized aluminum faceplate and 304 SST drive-rail for excellent corrosion performance
- Adjustable strikes made with 304 SST plates and a powder-coated zinc housing for additional corrosion resistance
- Compatible with standard 100 mm 3-hole US tail-driven system
 - Complimented by our complete RotoFasco Secura handle line
- 125 mm square drive system is also available

Advantages

- Single thumb-turn lever action extends all four locking points
- Increased adjustability in top and bottom locking points where doors are more prone to misalignment
- Mishandling device prevents hooks from being thrown while open to avoid damage to hardware and frame
- Easy installation due to the 4-point being supplied as a one piece assembly
- Opposing hook facings prevent door panel from being lifted off track and out of frame
- Meets ASTM F842 Grade 40 Forced Entry Testing (1,100 lbs.)
- Meets AAMA 910-93 Life Cycle Testing (2,500 cycles)
- Meets ASTM B117-97 Corrosion Resistance (1,000 hrs)

Adjustable Single-Point Striker



Adjustable Two-Point Stiker



Part Number	Description	Range	Box Quantity
805005	SPD 4PT MORTISE SQUARE-DRIVE VERSION		10
805007	SPD 4PT MORTISE BLADE-DRIVE VERSION		10
2000343	12MM ADJUSTABLE TITAN 2PT KEEPER SWS WHITE	0.500" - 0.625"	100
834436	12MM ADJUSTABLE TITAN 2PT KEEPER BLACK	0.500" - 0.625"	100
2000352	12MM ADJUSTABLE TITAN SP KEEPER SWS WHITE	0.500" - 0.750"	100
2000353	12MM ADJUSTABLE TITAN SP KEEPER BLACK	0.500" - 0.750"	100
2006998	20MM ADJUSTABLE TITAN 2PT KEEPER SWS WHITE	0.800" - 0.935"	100
834437	20MM ADJUSTABLE TITAN 2PT KEEPER BLACK	0.800" - 0.935"	100
2006999	20MM ADJUSTABLE TITAN SP KEEPER SWS WHITE	0.750" - 1.000"	100
2004692	20MM ADJUSTABLE TITAN SP KEEPER BLACK	0.750" - 1.000"	100